

BIPRO

TD6I72M 144-cell

435 - 455W

Bifacial Dual Glass
9BB Half-cut Mono Perc

SYSTEM & PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730 / UL 617: 0
- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environmental Management System
- ISO 45001: 2018 Occupational Health and Safety Management Systems




PERFORMANCE WARRANTY

12 Years
Quality Assurance

30 Years
Power Output Guarantee

Linear Performance Warranty



KEY FEATURES



9BB Half-cut Cell Technology

New circuit design, lower internal current, lower Rs loss
Ga doped wafer, attenuation <2% (1st year) / 0.45% (Linear)



Industry Leading High Yield

Bifacial PERC cell technology,
5%-25% more yield depends on different conditions



Excellent Anti-PID Performance

2 times of industry standard Anti-PID test



Wider Application

No water-permeability and high wear-resistance,
can be widely used in high-humid, windy and dusty area



IP68 Junction Box

High waterproof level

| Testing Condition | STC | NMOT |
|-------------------------------|-------|------|-------|------|-------|------|-------|------|-------|------|
| Maximum Power (Pmax/W) | | | | | | | | | | |
| Operating Voltage (Vmpp/V) | | | | | | | | | | |
| Operating Current (Impp/A) | | | | | | | | | | |
| Open-Circuit Voltage (Voc/V) | | | | | | | | | | |
| Short-Circuit Current (Isc/A) | | | | | | | | | | |
| Module Efficiency (%)Pmax/W) | 20.00 | | 20.20 | | 20.50 | | 20.70 | | 20.90 | |

STC: Irradiance 1000W/m², Spectra at AM1.5, Module Temperature 25°C. Power output tolerance: 0~+5W, Test uncertainty for Pmax: ±3%

NMOT: Irradiance 800W/m², Spectra at AM1.5, Ambient Temperature 20°C, Wind speed 1m/s