

BIPRO

TD7G60M **120-cell**

440 - 460W

Bifacial Dual Glass
10BB Half-cut Mono Perc

SYSTEM & PRODUCT CERTIFICATES

-
-
-
-




PERFORMANCE WARRANTY

12 Years
Quality Assurance

30 Years
Power Output Guarantee

Linear Performance Warranty



ELECTRICAL CHARACTERISTICS

	440	328	445	332	450	336	455	339	460	343
	34.35	32.1	34.53	32.2	34.70	32.4	34.87	32.6	35.04	32.7
	12.81	10.23	12.89	10.30	12.97	10.36	13.05	10.42	13.13	10.49
	40.99	38.6	41.16	38.7	41.33	38.9	41.50	39.1	41.67	39.2
	13.69	11.04	13.78	11.11	13.86	11.17	13.94	11.24	14.02	11.30
	20.30		20.50		20.70		21.00		21.20	

C.
C


REAR SIDE POWER GAIN(REFERENCE TO 445W FRONT)

	5%	10%	15%	20%	25%
	467	490	512	534	556
	34.53	34.53	34.53	34.53	34.53
	13.53	14.18	14.82	15.47	16.11
	41.16	41.16	41.16	41.16	41.16
	14.47	15.16	15.85	16.54	17.23

MECHANICAL CHARACTERISTICS

	Monocrystalline Silicon (10Busbar)
	120pcs in series (6*20)
	1914*1134*30mm (75.35*44.65*1.18inches)
	26.8kg (59.1lbs)
	2.0mm AR Coating Semi-tempered Glass
	2.0mm Glazed Semi-tempered Glass
	Anodized Aluminium Alloy
	IP68, 3 Bypass Diodes
	4mm ² (IEC), 12AWG(UL) 300mm in Length or Customized Length
	T01/LJQ-3-CSY/MC4/MC4-EV02

I-V CURVE



APPLICATION CONDITIONS

	1500V/DC
	-40°C~+85°C
	30A
	Class II
	Front side 5400Pa, Back side 2400Pa
	70%±5%

TEMPERATURE CHARACTERISTICS

	-0.35%/°C
	-0.26%/°C
	+0.048%/°C
	43±2°C

PACKING CONFIGURATION

	36	36(USA)
	864	684



The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, Suzhou Talesun Solar Technologies Co., Ltd. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.